



# Passive House Energy Standard


As modeled in the	РНРР				
Air Tightness:	.6 ACH @ 50pa				
Total Energy Demand (Source):	38 kBTU/SF/YR				
Cooling Demand (Site):	4.75 kBTU/SF/YR				
Heating Demand (Site):	4.75 kBTU/SF/YR				


(Passive House Planning Package)


<figure>























































of Insulation Materials									
Insulation Material	R-value R/inch	Density Ib/ft²	Emb. E MJ/kg	Emb. Carbon kgCO <sub>3</sub> /kg	Emb. Carbon kgCO <sub>2</sub> / ft <sup>2</sup> •R	Blowing Agent (GWP)	Bl. Agent kg/kg foam	Blowing Agent GWP/ bd-ft	Lifetin GWP ft2+R
Cellulose (dense-pack)	3.7	3.0	2.1	0.106	0.0033	None	0	N/A	0.003
Fiberglass batt	3.3	1.0	28	1.44	0.0165	None	0	N/A	0.016
Rigid mineral wool	4.0	4.0	17	1.2	0.0455	None	0	N/A	0.045
Polyisocyanurate	6.0	1.5	72	3.0	0.0284	Pentane (GWP=7)	0.05	0.02	0.031
Spray polyure- thane foam (SPF) – closed-cell (HFC-blown)	6.0	2.0	72	3.0	0.0379	HFC-245fa (GWP=1,030)	0.11	8.68	1.48
SPF - closed-cell (water-blown)	5.0	2.0	72	3.0	0.0455	Water (CO2) (GWP=1)	0	0	0.045
SPF - open-cell (water-blown)	3.7	0.5	72	3.0	0.0154	Water (CO2) (GWP=1)	0	0	0.015
Expanded polystyrene (EPS)	3.9	1.0	89	2.5	0.0307	Pentane (GWP=7)	0.06	0.02	0.03
Extruded polystyrene (XPS)	5.0	2.0	89	2.5	0.0379	HFC-134a1 (GWP=1,430)	0.08	8.67	1.77



































### Habitat for Humanity Passive House HVAC SYSTEM

Air Source Heat Pump

Mitsubishi Hyper-heat MSZ-MUZ FE 12


Zender ComfoAir 350 HRV


## Soil heat exchange system


Two 125' loops of 1" pex around the base of the footings filled with water/glycol mix & tied to Laing 30W AC Pump & water-to-air coil (~40F Temp Rise)


#### Solar Hot Water


Sunward Solar water heating system mounted on roof with 40g electric hot water heater as back-up











#### Habitat for Humanity Passive House HVAC SYSTEM - IAQ

The levels of CO2 in the air and potential health problems are:

250 - 350 ppm – background (normal) outdoor air level


350- 1,000 ppm - typical level found in occupied spaces with good air exchange.


1,000 – 2,000 ppm - level associated with complaints of drowsiness and poor air.


2,000 – 5,000 ppm – level associated with headaches, sleepiness, and stagnant, stale, stuffy air. Poor concentration, loss of attention, increased heart rate and slight nausea may also be present.


>5,000 ppm – Exposure may lead to serious oxygen deprivation resulting in permanent brain damage, coma and even death.


Wisconsin's Department of Health



























































































































































http://passipedia.passiv.de